



## T1x Treadmill

- Low 19 cm / 7.5" step-on height for easy accessibility
- WiFi connectivity accommodates optional Matrix Asset Management system and Workout Tracking Network
- Large LED display provides easy viewing and easy-to-use controls
- Optional: An ideal addition for facilities that cater to older individuals or people with limited abilities, our sturdy, steel handrails help ensure secure ingress and egress from the treadmill.
- Matrix 3.0 Hp AC motor with Dynamic Response Drive System fine-tunes response based on footfall pattern for a smooth, consistent, natural workout
- xID single-point user sign-in offers a seamless personal experience
- Ultimate Deck System for superior performance and durability

CONSOLE	
SECONDARY DATA DISPLAY	No
DISPLAY TYPE	Alphanumeric LED
DISPLAY FEEDBACK	Elapsed Time, Time Remaining, Distance, Calories, Speed, Incline, Pace, Heart Rate
USER-DEFINED MULTI-LANGUAGE DISPLAY	Accessible only through manager menu: English, German, French, Italian, Spanish, Dutch, Portuguese, Japanese, Swedish, Finnish, Turkish, Polish
WORKOUTS	Manual, Rolling Hills, Fat Burn, 5k, Target HR, Gerkin Protocol
CSAFE READY-FITLINXX	No
PRO:IDIOM COMPATIBLE	Optional - add-on TV
FITTOUCH	No
IPTV COMPATIBLE	No
ONE-BUTTON START	Yes
ON-THE-FLY PROGRAM CHANGE	Yes
INTEGRATED VISTA CLEAR	No
FITCONNECTION	Yes
WIFI ENABLED	Optional
IPOD	Charging only
BLUETOOTH ENABLED	No
MULTIMEDIA PLAYBACK	No
PERSONAL FAN	No
WORKOUT TRACKING NETWORK COMPATIBLE	Yes
WEB CONNECTIVITY	No
ASSET MANAGEMENT COMPATIBLE	Yes
PERSONAL TRAINER PORTAL COMPATIBLE	No
USB PORT	Yes
VIRTUAL ACTIVE	No
PAUSE FUNCTION	Yes
READING RACK	No
FACILITY COMMUNICATION PORTAL/CALENDAR	No
RFID COMPATIBLE	No

DRIVE SYSTEM	
DRIVE SYSTEM	Matrix 3.0 hp AC Dynamic Response Drive System

FEATURES	
DECK TYPE	Ultimate hard-wax reversible 1" deck
RUNNING AREA	152 x 51 cm / 60" x 20"
STEP-ON HEIGHT	19 cm / 7.5"
TREAD SENSE	No
CROSSBAR CONTROLS	No
SPEED RANGE	0.8 - 20 km/h / 0.5 - 12 mph
CONTACT & TELEMETRIC HR	Yes
CUSHION SYSTEM	Ultimate Deck
BELT TYPE	Habasit, 2-ply commercial grade
INCLINE RANGE	0-15% (318-kg / 700-lb. thrust elevation motor)

TECH SPECS	
ASSEMBLED DIMENSIONS	215 x 85 x 142 cm / 84.6" x 33.5" x 56"
ELECTRICAL RECEPTACLE & PLUG	NEMA 220v 6-20R
POWER REQUIREMENTS	20-amp dedicated circuit required, non-looped grounded
MAX USER WEIGHT	158.8 kg / 350 lbs.
ASSEMBLED WEIGHT	152.8 kg / 336 lbs.
SHIPPING WEIGHT	171.5 kg / 377 lbs.